



## TECHNICAL DATA SHEET

**PROFESSIONAL SCREENING**

rev. 05/2020

PRODUCT IDENTIFICATION	<b>BASIC 180</b>
USE	ROLL UP SCREEN
MANUFACTURE	WOVEN
STIFFNESS	STIFF
AVAILABLE COLOURS	BLACK / GREY
COMPOSITION	FIBERGLASS: 38% PVC: 62%
MESH	18X16
WEIGHT	116 gr/mq +/- 2%
THICKNESS	mm 0,29 +/- 0,03
HOLE DIMENSIONS	mm 1,13 x 1,46 +/- 0,03
OPENNESS (% SUNLIGHT)	63%
ULTIMATE STRENGTH WARP	N/50mm 740
ULTIMATE STRENGTH FILL	N/50mm 590
PACKING	Cardboard tubes
WIDTHS	cm 80/100/120/140/160/170/180 200/220/240/260/280/320
ROLL LENGTH	m 90-200-300-500-1000
WELDING	HEAT-HIGH FREQUENCY-ULTRASONIC
HEAT RESISTANCE	Da -35°C a +80°C
FLAME RESISTANCE	CLASS 2 SELF-EXTINGUISHING
CLEANING	WATER AND SOAP
NOMINAL DATA	

**T.I.E. TESSITURA INDUSTRIALE EUROPEA S.P.A.**  
**LOCALITÀ PETRONA - 50038 SCARPERIA - FI - ITALIA**  
**TEL. 055.8494588 - FAX 055.8455255 - E-MAIL: TIE@RETTIE.COM**  
**COD. FISC. 04747410480 - P. IVA IT 04747410480 - REA N. 477486**  
**R.I. FIRENZE - CAPITALE SOCIALE EURO 1.500.000,00**